

MODEL OVERVIEW FLOODLIGHTS

Model	Effective luminous power	Power consumption	Rated voltage	Lamp weight	Lamp weight, incl. 10m cable, plug, handles, mount	Dimensions with DIN 14640 mount, incl. all handles, WxHxD	Dimensions without mount; without handles, WxHxD
LED, alternating current							
LED 90 AC	11,600 lumens*	108 W	100...277 V AC	4.3 kg	6.7 kg	303 x 345 x 158 mm	303 x 175 x 140 mm
LED 130 AC	19,000 lumens*	140 W	100...277 V AC	5.6 kg	7.7 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED 180 AC	23,100 lumens*	177 W	100...277 V AC	5.6 kg	7.7 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED, direct current							
LED 90 DC	11,600 lumens*	108 W	10...32 V DC	3.8 kg	6.2 kg	303 x 345 x 158 mm	303 x 175 x 140 mm
LED 130 DC	19,000 lumens*	140 W	10...32 V DC	5.3 kg	7.0 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED 180 DC	23,100 lumens*	184 W	10...32 V DC	5.3 kg	7.0 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
Halogen							
BS 1000	11,000 lumens*	1,000 W	230 V AC	2.8 kg	5.0 kg	288 x 320 x 145 mm	288 x 162 x 140 mm
FS 1000	10,900 lumens*	1,000 W	230 V AC	3.6 kg	6.0 kg	390 x 348 x 220 mm	315 x 285 x 175 mm
FS 1500	16,400 lumens*	1,500 W	230 V AC	4.5 kg	6.8 kg	450 x 348 x 220 mm	380 x 285 x 175 mm
HS 1500	16,200 lumens*	1,500 W	230 V AC	3.0 kg	4.8 kg	450 x 340 x 160 mm	390 x 220 x 160 mm

*LED lamps: approx. 50,000 hours of service, 4,000 Kelvin, Ra = >80

Special versions available: e.g. custom cable length, delivery without plug and attachments, different colour temperature (Kelvin), etc.



KARL *Meister* GmbH