

MODEL OVERVIEW FLOODLIGHTS

Model	Effective luminous power	Power consumption	Rated voltage	Lamp weight	Lamp weight, incl. 10m cable, plug, handles, mount	Dimensions with DIN 14640 mount, incl. all handles, WxHxD	Dimensions without mount; without handles, WxHxD
LED, alternating current							
LED 90 AC	15,100 lumens*	108 W	100...277 V AC	4.3 kg	6.7 kg	303 x 345 x 158 mm	303 x 175 x 140 mm
LED 130 AC	22,000 lumens*	140 W	100...277 V AC	5.6 kg	7.7 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED 180 AC	26,000 lumens*	177 W	100...277 V AC	5.6 kg	7.7 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED, direct current							
LED 90 DC	15,200 lumens*	108 W	10...32 V DC	3.8 kg	6.2 kg	303 x 345 x 158 mm	303 x 175 x 140 mm
LED 130 DC	22,000 lumens*	140 W	10...32 V DC	5.3 kg	7.0 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
LED 180 DC	26,000 lumens*	184 W	10...32 V DC	5.3 kg	7.0 kg	350 x 360 x 135 mm	350 x 210 x 135 mm
Halogen (from 2021/09/01: If available from remaining stock)							
BS 1000	11,000 lumens*	1,000 W	230 V AC	2.8 kg	5.0 kg	288 x 320 x 145 mm	288 x 162 x 140 mm
FS 1000	10,900 lumens*	1,000 W	230 V AC	3.6 kg	6.0 kg	390 x 348 x 220 mm	315 x 285 x 175 mm
FS 1500	16,400 lumens*	1,500 W	230 V AC	4.5 kg	6.8 kg	450 x 348 x 220 mm	380 x 285 x 175 mm
HS 1500	16,200 lumens*	1,500 W	230 V AC	3.0 kg	4.8 kg	450 x 340 x 160 mm	390 x 220 x 160 mm

*LED lamps: approx. 50,000 hours of service, 4,000 Kelvin, Ra = >80

Special versions available: e.g. custom cable length, delivery without plug and attachments, different colour temperature (Kelvin), etc.

21.08



KARL *Meister* GmbH